



Rostfrei ROSTFREI
Inox
Stainless
Steel

2 Type

- A** without dowel hole
- B*** with dowel hole

1

| d ₁ | d ₃ | d ₄ | d ₅ H11 | e | h | k | l |
|----------------|----------------|----------------|--------------------|-----|----|----|----|
| M 5 | 14 | 20 | 1,5 | 2,5 | 12 | 8 | 7 |
| M 6 | 16 | 24 | 1,5 | 2,5 | 14 | 10 | 8 |
| M 8 | 20 | 30 | 2 | 3 | 17 | 12 | 10 |
| M 10 | 28 | 36 | 3 | 4 | 20 | 14 | 12 |
| M 12 | 32 | 40 | 4 | 4 | 24 | 16 | 16 |

* not available from stock, requires a minimum order quantity

Specification

- Stainless Steel AISI 303 **NI**
matt shot-blasted
- *ISO-Fundamental Tolerances* → Page 1132
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

3

Information

The dowel bore d₅ in the DIN 6303 Stainless Steel-knurled nut is designed for the use of clamping or notch pins.

DIN 6303 knurled nuts with H7 bore and the size M12 are not provided for on the official standard sheet.

see also...

- *Stainless Steel-Knurled nuts GN 536* → Page 321

How to order

DIN 6303-M6-A-NI

| | |
|----------|----------------|
| 1 | d ₁ |
| 2 | Type |
| 3 | Material |