

Starters for Fluorescent Lamps

Ecoclick Starters



Product Description

- Range of premium-quality glow switch starters for igniting fluorescent lamps with electromagnetic ballast.

Product Benefits

- The only starter that offers fast, easy installation with no need to use any extra tools
- No irritation – even firmly stuck starters can be removed easily
- Eco-friendly, recyclable concept (free of lead and radioactivity)
- More than 25% longer lamp life; lower maintenance costs compared with lower-quality, non-IEC-compliant starters
- Optimal connectivity through brass components and oxidation-resistant brass pins

- Flame-retardant components and UV-resistant canister for additional safety and secure ignition (validated by Underwriters Laboratories UL)

Product Features


- Redesigned canister top with two installation notches into which the pins of another starter fit perfectly (patented innovation)
- Radioactive-free (patented) and lead-free (RoHS-compliant)
- Premium reliability with more than 10,000 safe switches
- 2-pin igniter in plastic (flame-retardant polycarbonate) canister with high-quality radio-interference suppression capacitor
- Well-defined preheat and peak voltage ensure proper ignition

Application

- Ignition of fluorescent lamps of all brands with conventional electromagnetic ballasts using TL-D (T8), TL (T12), TL mini and PL-L lamps
- S2 starters are suitable for I10/I30 V 4-22 W single applications, 220/240 V 4-6-8-15-18-22 W single applications and 220/240 V 4-22 W series applications. It is recommended for 220/240 V 18 W single applications for optimal performance
- S10 starters are suitable for 220/240 V I3 4-65 W single applications. It is required for 220/240 V I3 W single applications

System

- Starter replacement recommended when replacing fluorescent lamps



C	E
max.	max.
40.3	21.5

Type	Wattage	System Description	Voltage	Bulb finish	Additional Information	Packing type	Packing configuration	Colour of the Housing	Photo letter	Ordering number
S2	4-22W	SER	220-240V	WH	EUR	INO	12X25CT	White	B	8711500... <b>69750933</b>
S2	4-22W	SER	220-240V	WH	EUR	INO	12X25CT	White	B	<b>90310533</b>
S2	4-22W	SER	220-240V	WH	EUR	INO	20X10CT	White	B	<b>69750931</b>
S2	4-22W	SER	220-240V	WH	EUR	INO	20X25CT	White	B	<b>69750926</b>
S2	4-22W	SER	220-240V	WH	EUR	INO	32X25CT	White	B	<b>69750956</b>
S2	4-22W	SER	220-240V	WH	EUR	UNP	300	White	B	<b>69750929</b>
S2	4-22W	SER	220-240V	WH	EUR	UNP	1,000	White	B	<b>69750928</b>
S2	4-22W	SER	220-240V	WH	EUR	UNP	1,000	White	B	<b>69845228</b>
S10	4-65W	SIN	220-240V	WH	EUR	INO	12X25CT	White	A	<b>69769133</b>
S10	4-65W	SIN	220-240V	WH	EUR	INO	12X25CT	White	A	<b>90312933</b>
S10	4-65W	SIN	220-240V	WH	EUR	INO	20X10CT	White	A	<b>69769131</b>
S10	4-65W	SIN	220-240V	WH	EUR	INO	20X25CT	White	A	<b>69769126</b>
S10	4-65W	SIN	220-240V	WH	EUR	INO	32X25CT	White	A	<b>69769156</b>
S10	4-65W	SIN	220-240V	WH	EUR	UNP	300	White	A	<b>69769129</b>
S10	4-65W	SIN	220-240V	WH	EUR	UNP	1,000	White	A	<b>69769128</b>
S10	4-65W	SIN	220-240V	WH	EUR	UNP	1,000	White	A	<b>69847628</b>

Additional technical data

Product name	System Description	Ambient Temperature (°C [min.])	Ambient Temperature (°C [max.])	Capacitor	Pulse Voltage (V [min.])	Non Reclosure Voltage (V [min.])
S10 4-65W SIN 220-240V WH EUR	Single	-15	75	yes	900	140
S2 4-22W SER 220-240V WH EUR	Series	-15	75	yes	800	70

## Starters for Fluorescent Lamps

## Eclick Starters

## Logistic data

Product name	Packing type	Packing type description	Packs per outer box	Packing configuration
S10 4-65W SIN 220-240V WH EUR	UNP	Unpacked	1000	1000
S10 4-65W SIN 220-240V WH EUR	INO	-	300	12X25CT
S2 4-22W SER 220-240V WH EUR	INO	-	500	20X25CT
S2 4-22W SER 220-240V WH EUR	INO	-	300	12X25CT
S2 4-22W SER 220-240V WH EUR	UNP	Unpacked	1000	1000
S2 4-22W SER 220-240V WH EUR	INO	-	300	12X25CT
S2 4-22W SER 220-240V WH EUR BOX	INO	-	200	20X10CT
S2 4-22W SER 220-240V WH EUR	INO	-	800	32X25CT
S2 4-22W SER 220-240V WH EUR	UNP	Unpacked	1000	1000
S2 4-22W SER 220-240V WH EUR	UNP	Unpacked	300	300
S10 4-65W SIN 220-240V WH EUR	INO	-	500	20X25CT
S10 4-65W SIN 220-240V WH EUR	INO	-	800	32X25CT
S10 4-65W SIN 220-240V WH EUR	INO	-	300	12X25CT
S10 4-65W SIN 220-240V WH EUR	INO	-	200	20X10CT
S10 4-65W SIN 220-240V WH EUR	UNP	Unpacked	300	300
S10 4-65W SIN 220-240V WH EUR	UNP	Unpacked	1000	1000

Product name	Quantity per pack	Packing length (mm)	Packing width (mm)	Packing height (mm)	Gross weight per piece (g)	Net weight per piece (g)
S10 4-65W SIN 220-240V WH EUR	1	400	300	185	7.46	7.00
S10 4-65W SIN 220-240V WH EUR	1	231	231	137	8.07	7.00
S2 4-22W SER 220-240V WH EUR	1	230	230	225	7.48	7.00
S2 4-22W SER 220-240V WH EUR	1	230	230	135	8.16	7.00
S2 4-22W SER 220-240V WH EUR	1	400	300	193	7.74	7.00
S2 4-22W SER 220-240V WH EUR	1	230	230	135	8.16	7.00
S2 4-22W SER 220-240V WH EUR BOX	1	225	225	100	8.93	7.00
S2 4-22W SER 220-240V WH EUR	1	240	240	360	8.52	6.94
S2 4-22W SER 220-240V WH EUR	1	400	300	193	7.38	7.00
S2 4-22W SER 220-240V WH EUR	1	230	230	135	7.45	7.00
S10 4-65W SIN 220-240V WH EUR	1	231	231	227	7.96	7.00
S10 4-65W SIN 220-240V WH EUR	1	240	240	360	8.50	6.93
S10 4-65W SIN 220-240V WH EUR	1	230	230	135	8.16	7.00
S10 4-65W SIN 220-240V WH EUR	1	225	225	100	8.65	7.00
S10 4-65W SIN 220-240V WH EUR	1	230	230	135	7.45	7.00
S10 4-65W SIN 220-240V WH EUR	1	400	300	193	7.38	7.00

## Additional extended technical data

Product name	Name Extension	Execution	Cap-Base Information
S10 4-65W SIN 220-240V WH EUR	S10	White	2P
S2 4-22W SER 220-240V WH EUR	S2	White	2P